



A6 VRX EnergySaver

- The International Mechanical Code requires TYPE II hoods over commercial dishwashers, except where the heat and moisture loads from such appliances are incorporated into the HVAC system design or into the design of a separate removal system.
- The VRX system eliminates the need for the installation of a Type II Hood over Auto-Chlor commercial dishwashers.
- Reduces installation and construction costs by eliminating the need for a Type II hood.
- Reduces heating and cooling costs by eliminating vent hood make-up air and reducing the moisture and heat in your kitchen.
- Factory installed system features integrated controls and simple single source power supply for easy installation.
- Regularly scheduled 28-day service ensures sparkling results, minimizes mechanical problems and reduces operating costs
- Benefiting from more than 80 years of improvements and dishwashing experience and knowledge



Energy Efficient

- Exceeds Energy Star requirements
- Low temperature chemical sanitizing saves energy

**Total Service.
Total Satisfaction.**



Specifications

Cycle Time: 90 seconds
 Rated capacity: 36 cycles/hour
 45 second Wash and Rinse
 45 second Vapor Recovery
 Cold water supply flow: 2 GPM
 Consumption per rack: 1.2 Gal
 Cold water connection: 1/4" NPT
 VRX drain connection: 1" O.D. tube
 Heat Load to Room:

- High Temp
 - Latent 18,417
 - Sensible 5,793
- Low Temp
 - Latent 11,469
 - Sensible 3,732

